

SAFETY2U PRODUCT INTRODUCTION**Safety2u (S2U) Security Grille, Detention Lockset and Door**

NO.	PRODUCT CATEGORY
1.1	(S2U) ML.G.1L. SW (Single Leaf Swing) 1.1.1 DETENTION FRAME 1.1.2 DETENTION DOOR 1.1.3 DETENTION LOCKSET
1.2	(S2U) ML.G.2L. SW (Double Leaf Swing) 1.2.1 DETENTION FRAME 1.2.2 DETENTION DOOR 1.2.3 DETENTION LOCKSET
1.3	(S2U) ML. G.1L.SL (Single Leaf Sliding) 1.3.1 DETENTION FRAME 1.3.2 DETENTION DOOR 1.3.3 DETENTION LOCKSET
1.4	(S2U) ML.G.2L. SL (Double Leaf Sliding) 1.4.1 DETENTION FRAME 1.4.2 DETENTION DOOR 1.4.3 DETENTION LOCKSET
1.5	(S2U) Steel Grille Panel
2	Safety2u (S2U) Detention, Prison & Custodial
2.1	Southern Steel Detention Lockset 1070A
2.2	Southern Steel Detention Lockset 1010A
2.3	Southern Steel Detention Lockset 1080A
2.4	Southern Steel Detention Lockset 1030A
3	Safety2u (S2U) Security Solid Door
3.1	(S2U) ML. S.1L. SW (Single Leaf Swing) 3.1.1 DETENTION FRAME 3.1.2 DETENTION DOOR 3.1.3 DETENTION LOCKSET
3.2	(S2U) ML.S.1L.SL (Single Leaf Sliding) 3.2.1 DETENTION FRAME 3.2.2 DETENTION DOOR 3.2.3 DETENTION LOCKSET
3.3	(S2U) ML.S.2L. SW (Double Leaf Swing) 3.3.1 DETENTION FRAME 3.3.2 DETENTION DOOR 3.3.3 DETENTION LOCKSET
3.4	(S2U) ML.S.2L.SL (Double Leaf Sliding) 3.4.1 DETENTION FRAME 3.4.2 DETENTION DOOR 3.4.3 DETENTION LOCKSET
4	Safety2u (S2U) Security Window Grille
4.1	(S2U) Window Grille

25 June 202

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR				
1.1	Safety2u (S2U) ML.G.1L. SW: Security Grille (Single Leaf, Swing)				
1.1.1	<p>DETENTION FRAME: S2U ML.G.1L. SW Supply and install overall size 1050mm x 2100mm High overall size single leaf solid steel vertical bar grille door with SIRIM Manufacturer/Supplier. Door frame made up of Mild Steel (MS) Rectangular Hollow Section (RHS) size 100mm x 75mm x 3mm thick, come with Safety2u Detention Hinges (4 units), each hinge features cast stainless steel leaves with integral security stud and non-removable stainless- steel pin with Brass between its leaves. Finish Stainless Steel size 4-1/2" x 4-1/2"x 3/16", weight 0.68kg approximately c/w 3 years warranty. Include Safety2u Detention Bolt Keeper, dust box come with fasteners screws and rubber buffer to minimize door impact. Stopper hollow size (HS) 20mm x 20mm and is welded to the upper corner on the side of the door opening. Strut Bar of 20mm diameter mild steel round bar horizontally positioned and welded at bottom part of door frame posts. Anchor bars will be placed at the edges of the door frame. The length of the anchor bar is 200mm, and it is bent 75mm (from either side) to form an L shape, anchor bar has a diameter of 20mm and is placed along the edge of the door frame and grille panel. Standard Grille Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
1.1.2	<p>DETENTION DOOR: S2U ML.G.1L. SW Supply and install single leaf solid steel vertical bar grille door with SIRIM Manufacturer/Supplier. Detail drawing as described, comprising of Mild Steel (MS) flat bar size 50mm (Width) x 12mm (Thick) with vertical Mild Steel solid Round Bars of 20mm diameter (R20 @ 250N/mm²) spaced at 100mm centre to centre (c/c) running through punched holes (22mm diameter) of Mild Steel infill Horizontal Bracing Bars size 50mm (Width) x 12mm (Thick) all welded together. For immediate areas around the security lock mounting box, the MS Solid Round Bars are spaced at 50mm centre to centre. Safety2u Detention Mounting box and Service Plate come with Safety2u Detention Escutcheon and fastener screws. 150mm x 75mm high food tray opening. To be installed with approved Safety2u Detention Hinges. Standard Grille Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
1.1.3	<p>DETENTION LOCKSET: Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1010 ASTM Approved Mechanical Deadlock Lockset to Specialist's specification and detail drawing as described.</p> <p>Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1070 ASTM Approved Automatic Slam Shut Mechanical Lock come with Security Latch to Safety2u Specialist's specification and detail drawing as described.</p>				
	Carried To Collection				

H 25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR				
1.2	Safety2u (S2U) ML.G.2L. SW: Security Grille (Double Leaf, Swing)				
1.2.1	<p>DETENTION FRAME: S2U ML.G.2L. SW Supply and install overall size 1800mm x 2100mm High overall size double leaf solid steel vertical bar grille door with SIRIM Manufacturer/Supplier. Door frame made up of Mild Steel (MS) Rectangular Hollow Section (RHS) size 100mm x 75mm x 3mm thick, come with Safety2u Detention Hinges (4 units), each hinge features cast stainless steel leaves with integral security stud and non-removable stainless- steel pin with Brass between its leaves. Finish Stainless Steel size 4-1/2" x 4-1/2"x 3/16", weight 0.68kg approximately c/w 3 years warranty. Include Safety2u Detention Bolt Keeper, dust box come with fasteners screws and rubber buffer to minimize door impact. Stopper hollow size (HS) 20mm x 20mm and is welded to the upper corner on the side of the door opening. Strut Bar of 20mm diameter mild steel round bar horizontally positioned and welded at bottom part of door frame posts. Anchor bars will be placed at the edges of the door frame. The length of the anchor bar is 200mm, and it is bent 75mm (from either side) to form an L shape, anchor bar has a diameter of 20mm and is placed along the edge of the door frame and grille panel. Standard Grille Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
1.2.2	<p>DETENTION DOOR: S2U ML.G.2L. SW Supply and install double leaf solid steel vertical bar grille door with SIRIM Manufacturer/Supplier. Detail drawing as described, comprising of Mild Steel (MS) flat bar size 50mm (Width) x 12mm (Thick) with vertical Mild Steel solid Round Bars of 20mm diameter (R20 @ 250N/mm²) spaced at 100mm centre to centre (c/c) running through punched holes (22mm diameter) of Mild Steel infill Horizontal Bracing Bars size 50mm (Width) x 12mm (Thick) all welded together. For immediate areas around the security lock mounting box, the MS Solid Round Bars are spaced at 50mm centre to centre. Safety2u Detention Mounting box and Service Plate come with Safety2u Detention Escutcheon and fastener screws. To be installed with approved Safety2u Detention Hinges and Safety2u Detention Head and Footbolt. Standard Grille Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
1.2.3	<p>DETENTION LOCKSET: Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1010 ASTM Approved Mechanical Deadlock Lockset to Specialist's specification and detail drawing as described.</p> <p>Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1080 ASTM Approved Mechanical Deadlock Lockset to Specialist's specification and detail drawing as described.</p>				
	Carried To Collection				

25 June 20

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR				
1.3	Safety2u (S2U) ML.G.1L.SL: Security Grille (Single Leaf, Sliding)				
1.3.1	DETENTION FRAME: S2U ML.G.1L.SL Supply and install single leaf sliding cell door, overall size 900mm x 2100mm high, SIRIM Manufacturer/Supplier, complete with Door frame made up of Mild Steel (MS) Rectangular Hollow Section (RHS) size 100mm x 75mm x 3mm thick. Strut Bar of 20mm diameter mild steel round bar horizontally positioned and welded at bottom part of door frame posts. Including all necessary sliding tracks, track guide, steel roller and Safety2u Detention Strike Plate come with fasteners screws and rubber buffer to minimize door impact. Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.				
1.3.2	DETENTION DOOR: S2U ML.G.1L.SL Supply and install single leaf sliding cell door, SIRIM Manufacturer/Supplier. Comprising of Mild Steel (MS) flat bar size 50mm (Width) x 12mm (Thick) with vertical Mild Steel solid Round Bars of 20mm diameter (R20 @ 250N/mm ²) spaced at 100mm centre to centre (c/c) running through punched holes (22mm diameter) of Mild Steel infill Horizontal Bracing Bars size 50mm (Width) x 12mm (Thick) all welded together. For immediate areas around the security lock mounting box, the MS Solid Round Bars are spaced at 50mm centre to centre. Safety2u Detention Mounting box and Service Plate come with Safety2u Detention Escutcheon and fastener screws. Including all necessary sliding tracks, track guide, steel roller. Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.				
1.3.3	DETENTION LOCKSET: Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1030 Automatic Deadlock and Safety2u Specialist's specification and detail drawing as described.				
	Carried To Collection				

25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR				
1.4	Safety2u (S2U) ML.G.2L.SL: Security Grille (Double Leaf, Sliding)				
1.4.1	<p>DETENTION FRAME: S2U ML.G.2L.SL Supply and install double leaf sliding cell door, overall size 1800m x 2100mm high, SIRIM Manufacturer/Supplier, complete with Door frame made up of Mild Steel (MS) Rectangular Hollow Section (RHS) size 100mm x 75mm x 3mm thick. Strut Bar of 20mm diameter mild steel round bar horizontally positioned and welded at bottom part of door frame posts. Including all necessary sliding tracks, track guide, steel roller, Safety2u Detention Strike Plate come with fasteners screws and rubber buffer to minimize door impact. Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
1.4.2	<p>DETENTION DOOR: S2U ML.G.2L.SL Supply and install double leaf sliding cell door, SIRIM Manufacturer/Supplier. Comprising of Mild Steel (MS) flat bar size 50mm (Width) x 12mm (Thick), with vertical Mild Steel solid Round Bars of 20mm diameter (R20 @ 250N/mm²) spaced at 100mm centre to centre (c/c) running through punched holes (22mm diameter) of Mild Steel infill Horizontal Bracing Bars size 50mm (Width) x 12mm (Thick) all welded together. For immediate areas around the security lock mounting box, the MS Solid Round Bars are spaced at 50mm centre to centre. Safety2u Detention Mounting box and Service Plate come with Safety2u Detention Escutcheon and fastener screws. Including all necessary sliding tracks, track guide, steel roller and Safety2u Detention Head and Footbolt. Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
1.4.3	<p>DETENTION LOCKSET: Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1030 Automatic Deadlock and Safety2u Specialist's specification and detail drawing as described.</p>				
	Carried To Collection				

25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
1.5	<p>Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR</p> <p>Safety2u (S2U) Steel Grille Panel</p> <p>Safety2u (S2U) Prepare shop drawing, supply and install overall size 3000mm x 3000mm high solid steel grille comprising of 20mm diameter with SIRIM Manufacturer/Supplier, solid steel vertical bar at 100mm centre to centre welded through 75mm x 20mm thick steel frame. For immediate areas around the security lock mounting box, the MS Solid Round Bars are spaced at 50mm centre to centre. Tail cast in concrete (monolithic) complete with 1050mm x 2100mm high solid grille door (measured separately). Anchor bars will be placed at the edges of the door frame. The length of the anchor bar is 200mm, and it is bent 75mm (from either side) to form an L shape, anchor bar has a diameter of 20mm and is placed along the edge of the grille panel. Including all necessary welding, drilling and Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
	Carried To Collection				

25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR				
2	Safety2u (S2U) Detention, Prison & Custodial				
2.1	<p>Southern Steel Detention Lockset 1070A</p> <p>Safety2u (S2U) Supply and install Southern Steel High Security Detention Lockset 1070A ASTM Approved Automatic Slam Shut Mechanical Lock size 9" L x 5" H x 1-1/2" TK, weight 11 lbs. stainless steel latch bolt with (2) 1/4", come with SECURITY LATCH deadlock actuator size 3/4" x 1/2" diameter case-hardened steel insert pins, silicon bronze/copper alloy paracentric cylinder with approved ASTM F-1577-96 (mechanical release operation cycle test, cylinder test, mechanical release force test, horizontal impact test, testing on fire doors) Certified Impact Test Grade 1 with single cylinder.</p>				
2.2	<p>Southern Steel Detention Lockset 1010A</p> <p>Safety2u (S2U) Supply and install Southern Steel High Security Detention Lockset 1010A Mechanical Deadlock size 4.4" L x 3.15" H x 1.35" TK, weight 4.5 lbs., steel lockbolt, silicon bronze/copper alloy cylinder with approved ASTM F-1577-01 (mechanical release operation cycle test, cylinder test, mechanical release force test, horizontal impact test) Certified impact test-grade 1 with double cylinder.</p>				
2.3	<p>Southern Steel Detention Lockset 1080A</p> <p>Safety2u (S2U) Supply and install Southern Steel Detention Lockset 1080A Series Mechanical Deadlock size 5-1/2" L x 3-7/8" H x 1-1/2" TK, weight 7 lbs., steel lockbolt, silicon bronze/copper alloy cylinder with approved ASTM F-1577-01 (mechanical release operation cycle test, cylinder test, mechanical release force test, horizontal impact test) Certified impact test-grade 1 with double cylinder.</p>				
2.4	<p>Southern Steel Detention Lockset 1030A</p> <p>Safety2u (S2U) Supply and install Southern Steel High Security Detention Lockset 1030A Automatic Deadlock size 10" H x 3-1/2" W x 1-1/2" TK, weight 12 lbs. Key activated unlocking. Hook bolt snap locks upon closing. Final 3/8" of door travel pushes plunger pin against door jamb and deadlocks.</p>				
	Carried To Collection				

25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR				
3	Safety2u (S2U) Security Solid Door				
3.1	Safety2u (S2U) ML.S.1L. SW: Steel Panel Door (Single Leaf, Swing)				
3.1.1	<p>DETENTION FRAME: S2U ML.S.1L. SW Supply and install security steel panel door High overall size 1050mm x 2100mm as described. Door frame made up of Mild Steel (MS) Rectangular Hollow Section (RHS) size 100mm x 75mm x 3mm thick, come with Safety2u Detention Hinges (4 units), each hinge features cast stainless steel leaves with integral security stud and non-removable stainless steel pin with Brass between its leaves. Finish Stainless Steel size 4-1/2" x 4-1/2"x 3/16", weight 0.68kg approximately c/w 3 years warranty. Include Safety2u Detention Bolt Keeper, dust box come with fasteners screws and rubber buffer to minimize door impact. Stopper hollow size (HS) 20mm x 20mm and is welded to the upper corner on the side of the door opening. Strut Bar of 20mm diameter mild steel round bar horizontally positioned and welded at bottom part of door frame posts. Anchor bars will be placed at the edges of the door frame. The length of the anchor bar is 200mm, and it is bent 75mm (from either side) to form an L shape, anchor bar has a diameter of 20mm and is placed along the edge of the door frame. Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
3.1.2	<p>DETENTION DOOR: S2U ML.S.1L. SW Supply and install security steel panel door described compromises of 3mm thick steel plate on both sides infill with mineral wood insulation, view opening steel plated sliding closer with security key system, padlock and 150mm x 75mm high food tray opening. Include Safety2u Detention Mounting box and Service Plate come with Safety2u Detention Escutcheon and fastener screws. To be installed with approved Safety2u Detention Hinges. 20mm diameter steel door handle. Comprising of steel plate on both sides, steel frame, apply with Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint on exposed surfaces of steel works.</p>				
3.1.3	<p>DETENTION LOCKSET: Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1010 ASTM Approved Mechanical Deadlock Lockset and Safety2u Specialist's specification and detail drawing as described.</p> <p>Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1070 ASTM Approved Automatic Slam Shut Mechanical Lock come with Security Latch and Safety2u Specialist's specification and detail drawing as described.</p>				
	Carried To Collection				

25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	<u>Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR</u>				
	<u>Safety2u (S2U) Security Solid Door</u>				
3.2	<u>Safety2u (S2U) M.L.S. 1L.SL: Steel Sliding Door (Single Leaf, Sliding)</u>				
3.2.1	<p>DETENTION FRAME: S2U M.L.S.1L.SL Supply and install security steel panel door High overall size 900mm x 2100mm as described. Door frame made up of Mild Steel (MS) Rectangular Hollow Section (RHS) size 100mm x 75mm x 3mm thick, Stopper hollow size (HS) 20mm x 20mm is welded to the corner on the side of the door opening. Strut Bar of 20mm diameter mild steel round bar horizontally positioned and welded at bottom part of door frame posts. Including all necessary sliding tracks, track guide, steel roller and Safety2u Detention Strike Plate come with fasteners screws and rubber buffer to minimize door impact. Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
3.2.2	<p>DETENTION DOOR: S2U M.L.S.1L.SL Supply and install security steel panel door described compromises of 3mm thick steel plate on both sides infill with mineral wood insulation. 20mm diameter steel door handle. Safety2u Detention Mounting box and Service Plate come with Safety2u Detention Escutcheon and fastener screws. Including all necessary sliding tracks, track guide, steel roller. Comprising of steel plate on both sides, steel frame, apply with Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint on exposed surfaces of steel works.</p>				
3.2.3	<p>DETENTION LOCKSET: Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1030 Automatic Deadlock and Safety2u Specialist's specification and detail drawing as described.</p>				
	Carried To Collection				

25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR				
	Safety2u (S2U) Security Solid Door				
3.3	Safety2u (S2U) ML.S.2L. SW: Steel Panel Door (Double Leaf, Swing)				
3.3.1	<p>DETENTION FRAME: S2U ML.S.2L. SW Supply and install security steel panel door High overall size 1800mm x 2100mm as described. Door frame made up of Mild Steel (MS) Rectangular Hollow Section (RHS) size 100mm x 75mm x 3mm thick, come with Safety2u Detention Hinges (4 units), each hinge features cast stainless steel leaves with integral security stud and non-removable stainless-steel pin with Brass between its leaves. Finish Stainless Steel size 4-1/2" x 4-1/2"x 3/16", weight 0.68kg approximately c/w 3 years warranty. Include Safety2u Detention Bolt Keeper, dust box come with fasteners screws and rubber buffer to minimize door impact. Stopper hollow size (HS) 20mm x 20mm and is welded to the upper corner on the side of the door opening. Strut Bar of 20mm diameter mild steel round bar horizontally positioned and welded at bottom part of door frame posts. Anchor bars will be placed at the edges of the door frame. The length of the anchor bar is 200mm, and it is bent 75mm (from either side) to form an L shape, anchor bar has a diameter of 20mm and is placed along the edge of the door frame. Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
3.3.2	<p>DETENTION DOOR: S2U ML.S.2L. SW Supply and install security steel panel door as described compromises of 3mm thick steel plate on both sides infill with mineral wood insulation. Safety2u Detention Mounting box and Service Plate come with Safety2u Detention Escutcheon and fastener screws. To be installed with approved Safety2u Detention Hinges and Safety2u Detention Head and Footbolt. 20mm diameter steel door handle. Comprising of steel plate on both sides, steel frame, apply with Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint on exposed surfaces of steel works.</p>				
3.3.3	<p>DETENTION LOCKSET: Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1010 ASTM Approved Mechanical Deadlock Lockset and Safety2u Specialist's specification and detail drawing as described.</p> <p>Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1080 ASTM Approved Mechanical Deadlock Lockset and Safety2u Specialist's specification and detail drawing as described.</p>				
	Carried To Collection				

25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
	Safety2u (S2U) SECURITY GRILLE, DETENTION LOCKSET AND DOOR				
	Safety2u (S2U) Security Solid Door				
3.4	Safety2u (S2U) ML.S.2L.SL: Steel Sliding Door (Double Leaf, Sliding)				
3.4.1	<p>DETENTION FRAME: S2U ML.S.2L.SL Supply and install security steel panel door High overall size 1800mm x 2100mm as described. Door frame made up of Mild Steel (MS) Rectangular Hollow Section (RHS) size 100mm x 75mm x 3mm thick. Strut Bar of 20mm diameter mild steel round bar horizontally positioned and welded at bottom part of door frame posts. Including all necessary sliding tracks, track guide, Safety2u Detention Strike Plate come with fasteners screws and rubber buffer to minimize door impact. Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint.</p>				
3.4.2	<p>DETENTION DOOR: S2U ML.S.2L.SL Supply and install security steel panel door described compromises of 3mm thick steel plate on both sides infill with mineral wood insulation. 20mm diameter steel door handle. Safety2u Detention Mounting box and Service Plate come with Safety2u Detention Escutcheon and fastener screws. Including all necessary sliding tracks, track guide, steel roller and Safety2u Detention Head and Footbolt. Comprising of steel plate on both sides, steel frame, apply with Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint on exposed surfaces of steel works.</p>				
3.4.3	<p>DETENTION LOCKSET: Ditto Detention Frame and Detention Door come with Southern Steel High Security Detention Lockset 1030 Automatic Deadlock and Safety2u Specialist's specification and detail drawing as described.</p>				
	Carried To Collection				

#25 June 2026

BUILDING WORKS

Ref.	Description	Unit	Qty	Rate [RM]	Amount [RM]
4	Safety2u (S2U) WINDOW				
4.1	Safety2u (S2U) Security Window Grille Safety2u (S2U) Prepare shop drawing, supply and install the following fixed window grille comprising of 20mm diameter solid steel vertical bar at 100mm centre to centre until cast in concrete (monolithic) complete with expanded metal. 50mm x 12mm thick mild steel flat bar, and including all necessary welding, drilling and Standard Coating undercoat oxide Finish coat Equivalent Gloss Paint. 1250mm x 600mm high overall size 2700mm x 600mm high overall size 900mm x 900mm high overall size 2700mm x 900mm high overall size 1350mm x 1000mm high overall size				
	Carried To Collection				

25 June 2026